



Features

- Fully sealed assembly
- Updated and efficient design
- Structural waterproofing
- Mounting adapters available
- Available "Dusk to Dawn" sensor



Applications

- Roadways
- Commercial locations
- Outdoor overhead


Specification

Solar panel	6V 15W poly
Lithium battery	15Ah
Charging time	4-6H
Working time	24-36H
Working mode	Radar sensor + light control + time control + remote control
Power	300W
Color temperature	6500K
Lamp Size	420*420mm
Color box size	42*13*42cm
Material	ABS+PC
IP Grade	IP65
Light source type	120PCS 2835SMD
Lifespan	50000H
PCS/CTN	5
CTN weight	18KG
CTN size	67*44*44cm
Warranty	2 years



Features

- Fully sealed assembly
- Updated and efficient design
- Structural waterproofing
- Mounting adapters available
- Available "Dusk to Dawn" sensor



Applications

- Roadways
- Commercial locations
- Outdoor overhead

Specification

Solar panel	6V 15W poly
Lithium battery	15Ah
Charging time	4-6H
Working time	24-36H
Working mode	Radar sensor + light control + time control + remote control
Power	300W
Color temperature	6500K
Lamp Size	350*350mm
Material	ABS
Color box size	42*13*42cm
IP Grade	IP65
Light source type	336PCS 2835SMD
Lifespan	50000H
PCS/CTN	5
CTN weight	18KG
CTN size	67*44*44cm
Warranty	2 years



Features

- Fully sealed assembly
- Updated and efficient design
- Structural waterproofing
- Mounting adapters available
- Available "Dusk to Dawn" sensor



Applications

- Roadways
- Commercial locations
- Outdoor overhead

Specification

Solar panel	6V 18W poly
Lithium battery	15Ah
Charging time	4-6H
Working time	24-36H
Working mode	Radar sensor + light control + time control + remote control
Power	400W
Color temperature	6500K
Lamp Size	460*460*135mm
Material	ABS
IP Grade	IP65
Light source type	360PCS 5730SMD
Lifespan	50000H
PCS/CTN	5
Warranty	2 years



Features

- Fully sealed assembly
- Updated and efficient design
- Structural waterproofing
- Mounting adapters available
- Available "Dusk to Dawn" sensor



Applications

- Roadways
- Commercial locations
- Outdoor overhead

Specification

Solar panel	6V 25W poly
Lithium battery	20Ah
Charging time	4-6H
Working time	24-36H
Working mode	Radar sensor + light control + time control + remote control
Power	500W
Color temperature	6500K
Lamp Size	520*520mm
Color box size	55.5*13*55cm
Material	ABS
IP Grade	IP65
Light source type	400PCS 2835SMD
Lifespan	50000H
PCS/CTN	5
CTN weight	25KG
CTN size	67*57*57cm
Warranty	2 years